

Wedding Band Maker Instructions

To begin:

- After reading these instructions, click the X on the upper right of the box below to enlarge to the full screen. You can find this button beside the magnifier icon.
- **To move the ring:** If you left click and hold while moving the mouse, you can rotate the ring to see from top, sides and bottom. If you right click and hold while moving the mouse you can move across the page. Practice a few times before beginning.
- **Ring Size:** Start by choosing your ring size. If you are unsure you can estimate. We will discuss the final ring size and details before the order is placed and I will provide a more accurate quote based on size then.
- **Type:** This drop down menu allows you to choose the shank profile.
- **Metal:** This allows you to see the ring in white, rose or yellow gold.
- **Ring width:** Choose the width you like. For example a popular width for women is 2mm and men is 5mm.
- **Ring thickness:** The most popular thickness is 1.4 or 1.5mm. But if you like the band a little heavier, 1.8-2mm is quite thick.
- **Finish:** Polished or satin. You won't see this change in the final rendering. However your finish choice will be done by hand.
- **Texture:** Do you want your ring smooth, hammered, or lightly hammered.
- Lastly, you will enter your name, phone number, and email address.
- Once you have chosen all of your customizations and are happy with the look, you can send me the file by clicking on the blue box. I will receive your selections for the ring via email and will contact you to confirm your order.
- Please note the price shown for the ring is an estimation and I will confirm the quote with you before moving forward. You are under no obligation to purchase the ring if you send your customization. This is for a quote only.